

## Lynx D

Lynx-D Standard 26w/830 G24d-3

0025797

Image not found.

### Product features

- Compact Double bend 2-pin base lamp



## PRODUCT OVERVIEW

IPC Code	0025797
Product name	Lynx-D Standard 26w/830 G24d-3
Technology	Compact Fluorescent
Watt (Rated) (W)	26
Lamp shape	CFLni
Cap/Base	G24d-3
Lamp finish	Frosted
Fixture rating	Open
General application	Education,Hospitality,Logistics & Industry,Museums & Galleries,Office,Retail,Residential & Consumer
Certifications	EUERL036
ETIM Class	EC000087
Luminous flux (lm)	1780
Colour temperature (K)	3000
Light colour	Warm White Deluxe
CRI (Ra)	82
Wattage (W)	26
Product Voltage (V)	220
Dimmable	No
Average life (Nominal) (h)	12000
Product EAN number	5410288257976

## DATA TABLE

### General data

IPC Code	0025797
Product name	Lynx-D Standard 26w/830 G24d-3
Technology	Compact Fluorescent
Watt (Rated) (W)	26
Lamp shape	CFLni
Cap/Base	G24d-3
Lamp finish	Frosted
Fixture rating	Open
General application	Education,Hospitality,Logistics & Industry,Museums & Galleries,Office,Retail,Residential & Consumer

## Lynx D

*Lynx-D Standard 26w/830 G24d-3*

0025797

Certifications	EUERL036
ETIM Class	EC000087

### Optical data

Luminous flux (lm)	1780
Luminous flux (Rated) (lm)	1780
Rated lamp efficacy 100h 50Hz at 25°C (lm/W)	66
Rated lamp efficacy 100h 50Hz at optimum temp. (lm/W)	66
Rated lamp efficacy 100h HF at 25°C (lm/W)	66.00
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	3000
Light colour	Warm White Deluxe
Colour Code	War
CRI (Ra)	82
Adjustable chromaticity	N
Rated lumen maint. factor (%) at 2000 h 50Hz	85
Rated lumen maint. factor (%) at 4000 h 50Hz	78
Rated lumen maint. factor (%) at 8000 h 50Hz	75

### Electrical data

Wattage (W)	26
Starting time (max) (s)	<10s
Warm-up time to 60% of full light (max) (s)	60
Current (A)	0.325
Product Voltage (V)	220
Ignition voltage (V)	198
Control gear required	Yes
Transformer required	Yes
Dimmable	No
Lamp Energy Label (class)	A
Energy efficiency level	A
kWh per 1000 hours burning time	28

### Lifetime data

Average life (Nominal) (h)	12000
Average life (Rated) (h)	12000
Rated survival factor (%) at 2000 h 50Hz	96
Rated survival factor (%) at 4000 h 50Hz	90
Rated survival factor (%) at 6000 h 50Hz	80
Rated survival factor (%) at 8000 h 50Hz	72

### Physical data

Max. Length base to base (mm) - A	15.6
-----------------------------------	------

## Lynx D

*Lynx-D Standard 26w/830 G24d-3*

0025797

Max. Lamp Diameter (mm) - D	35
Weight (kg)	0.055

### Packaging

Single packaging type	Carton
Product EAN number	5410288257976
Packaging single length / height (cm)	17.83
Packaging single width (cm)	3.57
Packaging single depth (cm)	3.5
DUN14 (inner)	25410288257970
Units per inner package	10
Packaging inner length / height (cm)	18.93
Packaging inner width (cm)	19.07
Packaging inner depth (cm)	7.9
DUN14 (outer)	15410288257973
Units per outer package	50
Packaging outer length / height (cm)	42.9
Packaging outer width (cm)	22.0
Packaging outer depth (cm)	22.1

### Safety data

Lamp mercury content (mg)	2.50
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Intended purpose	General lighting
Dry applications use only	No
Suitable for household illumination	Yes
Suitable for accent lighting	N/A

Lynx D

*Lynx-D Standard 26w/830 G24d-3*

0025797

