

## Lynx D

Lynx-D Superia 26W/840 G24D-3 SLV

0025915



### Product features

- Compact and high performance double bend 2-bend pin lamp, - Suitable for operation on electronic control gear (DE type) and magnetic ballast (D version), - Dimmable with suitable dimmer, - Excellent colour rendering, - Suitable for emergency lighting



## PRODUCT OVERVIEW

IPC Code	0025915
Product name	Lynx-D Superia 26W/840 G24D-3 SLV
Technology	Compact Fluorescent
Watt (Rated) (W)	26
Lamp shape	CFLni
Cap/Base	G24d-3
Lamp finish	Frosted
Fixture rating	Open
General application	Education,Hospitality,Logistics & Industry,Museums & Galleries,Office,Retail,Residential & Consumer
Certifications	EUERL036
ETIM Class	EC000087
E-number FI	4944114
E-number SE	8357368
Luminous flux (lm)	1800
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	82
Wattage (W)	26
Product Voltage (V)	220
Dimmable	No
Average life (Nominal) (h)	12000
Product EAN number	5410288259154

## DATA TABLE

### General data

IPC Code	0025915
Product name	Lynx-D Superia 26W/840 G24D-3 SLV
Technology	Compact Fluorescent
Watt (Rated) (W)	26
Lamp shape	CFLni
Cap/Base	G24d-3
Lamp finish	Frosted
Fixture rating	Open

## Lynx D

*Lynx-D Superia 26W/840 G24D-3 SLV*

0025915

General application	Education,Hospitality,Logistics & Industry,Museums & Galleries,Office,Retail,Residential & Consumer
Certifications	EUERL036
ETIM Class	EC000087
E-number FI	4944114
E-number SE	8357368

### Optical data

Luminous flux (lm)	1800
Luminous flux (Rated) (lm)	1800
Rated lamp efficacy 100h 50Hz at 25°C (lm/W)	66
Rated lamp efficacy 100h 50Hz at optimum temp. (lm/W)	66
Rated lamp efficacy 100h HF at 25°C (lm/W)	69.23
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	82
Adjustable chromaticity	N
Rated lumen maint. factor (%) at 2000 h 50Hz	85
Rated lumen maint. factor (%) at 4000 h 50Hz	78
Rated lumen maint. factor (%) at 8000 h 50Hz	75

### Electrical data

Wattage (W)	26
Starting time (max) (s)	10 Sec
Current (A)	0.42
Product Voltage (V)	220
Ignition voltage (V)	191
Control gear required	Yes
Transformer required	No
Dimmable	No
Lamp Energy Label (class)	A
Energy efficiency level	A
kWh per 1000 hours burning time	28

### Lifetime data

Average life (Nominal) (h)	12000
Average life (Rated) (h)	12000
Rated survival factor (%) at 2000 h 50Hz	96
Rated survival factor (%) at 4000 h 50Hz	90
Rated survival factor (%) at 6000 h 50Hz	80
Rated survival factor (%) at 8000 h 50Hz	72

## Lynx D

Lynx-D Superia 26W/840 G24D-3 SLV

0025915

Rated survival factor (%) at 12000 h 50Hz	50
Rated survival factor (%) at 16000 h 50Hz	71

### Physical data

Max. Length base to base (mm) - A	171
Max. Lamp Diameter (mm) - D	35
Weight (kg)	0.06


### Packaging

Single packaging type	Carton
Product EAN number	5410288259154
Packaging single length / height (cm)	17.3
Packaging single width (cm)	3.6
Packaging single depth (cm)	3.6
DUN14 (outer)	15410288259151
Units per outer package	10
Packaging outer length / height (cm)	18.4
Packaging outer width (cm)	8.0
Packaging outer depth (cm)	18.7

### Safety data

Lamp mercury content (mg)	2.5
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Intended purpose	General lighting
Dry applications use only	Yes
Suitable for household illumination	Yes

## TECHNICAL DRAWINGS



Lynx D

Lynx-D Superia 26W/840 G24D-3 SLV

0025915

