

ToLEDo Striplight ToLEDo ST 500mm 4.5W 420lm S14s 0026838

Product features

ToLEDo striplight S14s 500mm is a perfect retrofit solution to replace your old incandescent. With 25,000 hours life and delivering 420lm, the LED version is consuming only 4.5 watts against 60 watts for the incandescent version it means to replace. The S14s linear striplight is the best solution to upgrade your lighting (mirror lighting, bathroom, under cabinet...) and make some serious consumption saving. Backed by a 3 years warranty, this product is a real retrofit offering value for money. Main features: -Striplight linear, 500mm with S14s caps (60W replacement). -Life of 25,000 hours, 5W and delivering 420 lumen. -3 years warranty.









NOTES

undefined

PRODUCT OVERVIEW

| IPC Code | 0026838 |
|----------------------------|-------------------------------------|
| Product name | ToLEDo ST 500mm 4.5W 420lm S14s |
| Technology | LED |
| Watt (Rated) (W) | 4.5 |
| Lamp shape | Striplight |
| Cap/Base | S14s |
| Lamp finish | frosted |
| General application | Hospitality, Residential & Consumer |
| Certifications | 00 |
| E-number FI | 4740313 |
| Luminous flux (Im) | 420 |
| Colour temperature (K) | 2700 |
| Light colour | Homelight |
| CRI (Ra) | 80 |
| Colour Consistency (SDCM) | 6 |
| Wattage (W) | 4.5 |
| Average life (Nominal) (h) | 25000 |
| Product EAN number | 5410288268385 |

DATA TABLE

| General data |
|--------------|
|--------------|

| acriciai aata | |
|------------------|---------------------------------|
| IPC Code | 0026838 |
| Product name | ToLEDo ST 500mm 4.5W 420lm S14s |
| Technology | LED |
| Watt (Rated) (W) | 4.5 |
| Lamp shape | Striplight |
| Cap/Base | S14s |
| Lamp finish | frosted |



ToLEDo Striplight ToLEDo ST 500mm 4.5W 420lm S14s 0026838

| General application | Hospitality,Residential & Consumer |
|---|------------------------------------|
| Certifications | 00 |
| E-number FI | 4740313 |
| Optical data | |
| Luminous flux (Im) | 420 |
| Luminous flux (Rated) (Im) | 420 |
| Colour temperature (K) | 2700 |
| Light colour | Homelight |
| Colour Code | Hom |
| CRI (Ra) | 80 |
| Colour Consistency (SDCM) | 6 |
| Adjustable chromaticity | N |
| Lumen maintenance at end of nominal life (%) | 70 |
| Electrical data | |
| Wattage (W) | 4.5 |
| Equivalent watt (W) | 60 |
| Starting time (max) (s) | 0.05 |
| Warm-up time to 60% of full light (max) (s) | < 1s => 60% |
| Current (A) | 0.042 |
| Mains voltage (V) | 220-240V~ |
| Lamp power factor | 0.5 |
| Mains frequency (Hz) | 50 |
| Control gear required | No |
| No. Of switching cycles before premature failures | 20000 |
| Transformer required | No |
| Lamp Energy Label (class) | A+ |
| Energy efficiency level | A+ |
| kWh per 1000 hours burning time | 5 |
| Lifetime data | |
| Average life (Nominal) (h) | 25000 |
| Average life (Rated) (h) | 25000 |
| | |
| Physical data | |
| Max. Lamp Diameter (mm) - D | 26 |
| Weight (kg) | 0.094 |
| | |
| Packaging | |
| Single packaging type | Carton |
| Product EAN number | 5410288268385 |
| Packaging single length / height (cm) | 53.0 |
| Packaging single width (cm) | 5.3 |
| Packaging single depth (cm) | 3.4 |
| DUN14 (inner) | 25410288268389 |
| Units per inner package | 6 |
| | |



ToLEDo Striplight ToLEDo ST 500mm 4.5W 420lm S14s 0026838

| Packaging inner length / height (cm) | 16.5 |
|--------------------------------------|----------------|
| Packaging inner width (cm) | 7.8 |
| Packaging inner depth (cm) | 53.7 |
| DUN14 (outer) | 15410288268382 |
| Units per outer package | 60 |
| Packaging outer length / height (cm) | 42.5 |
| Packaging outer width (cm) | 36.0 |
| Packaging outer depth (cm) | 56.5 |
| | |

Safety data

| Breakage cleaning instructions | Not applicable |
|--|------------------|
| Recommendation for disposal at end of life | Not applicable |
| Special purpose lamp | No |
| Intended purpose | General lighting |
| Suitable for household illumination | Yes |
| Suitable for accent lighting | yes |

