

## Start Bulkhead LED IP65 Oval

### START BULKHEAD LED IP65 OVAL 4K 1500LM

#### 0049179



#### Product features

- "LED exterior bulkhead, oval, comes with 2m cable, white polycarbonate body, 1495LM, 18W, 83lm/W, 4000K, Driver Current 135mA, CRI80, , non-dimmable, IP65, IK08, 25000hrs (L70), (LxWxD) 333x223x78mm"



### PRODUCT OVERVIEW

IPC Code	0049179
Product name	START BULKHEAD LED IP65 OVAL 4K 1500LM
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Fixture rating	Enclosed
General application	Logistics & Industry, Residential & Consumer
ETIM Class	EC002892
E-number SE	7505124
Fixture luminous flux (lm)	1495
Luminous flux (lm)	1495
Luminaire efficacy (lm/W)	83.1
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG1
Total power consumption (W)	18
Electrical protection	Class II
Dimmable	No
Housing colour	White
IP rating	IP65
IK rating	IK08
Product EAN number	5410288491790

### DATA TABLE

#### General data

IPC Code	0049179
Product name	START BULKHEAD LED IP65 OVAL 4K 1500LM
Technology	LED
Housing	PC Polycarbonate

## Start Bulkhead LED IP65 Oval

*START BULKHEAD LED IP65 OVAL 4K 1500LM*  
0049179

Mount	Ceiling surface mounting
Fixture rating	Enclosed
General application	Logistics & Industry, Residential & Consumer
Operating temperature range (°C)	-10°C - 40°C
ETIM Class	EC002892
E-number SE	7505124

### Optical data

Fixture luminous flux (lm)	1495
Luminous flux (lm)	1495
Luminaire efficacy (lm/W)	83.1
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG1

### Electrical data

Total power consumption (W)	18
Current (A)	0.09
Mains voltage (V)	220-240V~
Electrical protection	Class II
Dimmable	No
Drive current (mA)	135
Inrush Duration (µs)	600
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	18
Max. Luminaires per 16A C Breaker	30

### Lifetime data

Lumen maintenance - L70 B50	25000
Lumen maintenance - L70 B20	23000
Lumen maintenance - L70 B10	21000
Lumen maintenance - L80 B50	19000
Lumen maintenance - L80 B20	17500
Lumen maintenance - L80 B10	16000

### Physical data

Housing colour	White
IP rating	IP65
IK rating	IK08
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	78
Nominal Product Width (mm)	223
Nominal Product Height (mm)	333
Weight (kg)	0.98

## Start Bulkhead LED IP65 Oval

START BULKHEAD LED IP65 OVAL 4K 1500LM  
0049179

### Packaging


Single packaging type	Carton
Product EAN number	5410288491790
Packaging single length / height (cm)	34.5
Packaging single width (cm)	11.0
Packaging single depth (cm)	23.5
DUN14 (outer)	15410288491797
Units per outer package	6
Packaging outer length / height (cm)	71.0
Packaging outer width (cm)	35.0
Packaging outer depth (cm)	25.5

### PHOTOMETRY


0.5	2.20	E(0°) E(10°)	1438 50
1.0	4.41	E(0°) E(10°)	371 12
1.5	6.61	E(0°) E(10°)	198 6
2.0	8.82	E(0°) E(10°)	93 3
2.5	11.02	E(0°) E(10°)	59 2
3.0	13.23	E(0°) E(10°)	41 1

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 151.2°)





### TECHNICAL DRAWINGS




## Start Bulkhead LED IP65 Oval START BULKHEAD LED IP65 OVAL 4K 1500LM 0049179


**SYLVANIA** 0049179


 This luminaire contains built-in LED lamps

 } LED


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built-in LED lamps

 } LED

The lamps cannot be changed in the luminaire.

**SYLVANIA** 0049179 

874/2012