TUNGSRAM

Innovation is our heritage EST. 1896





IP44 Diffuser Downlight LED Downlight D1 TU 6 IP44 18W 830 S 93109216

Product information

Tungsram introduces the IP44 LED Diffuser Downlighters. There are a selection of sizes and colour temperature options to meet customer requirements. With this new range, lighting can be upgraded in key segments such as offices, commercial buildings, retail back of house areas and hospitality.



IP44 Diffuser Downlight LED Downlight D1 TU 6 IP44 18W 830 S 93109216

Product data

93109216
LED Downlight D1 TU 6 IP44 18W 830 S
TUNGSRAM - IP44 Diffuser Downlight - 1700lm - 18W - 3000K - 80CRI - 93109216[SKU] - Recessed
TUNGSRAM
Diffuser Downlight IP44
Downlighters
Public building, Office, Retail
15994100028175
LED
No sensor
No EM
Recessed
0,25
White, RAL9003
Dia 185 x Dia 185 x 63
-20
40
25
Passive
CE
5

Performance data

System power [W]	18
Nominal luminous flux [lm]	1700
Rated efficacy [lm/W]	94
Rated life L70/B50 [h]	50000
IP front (optical)	44
IP back (electrical)	20
IP Rating	20
Impact resistance (IK)	IK02

Photometrical data

Photometric distribution	Very Wide Flood
Nominal correlated colour temperature (CCT) [K]	3000
Colour rendering index (CRI) [Ra]	>=80
Nominal beam angle [°]	100
UGR value (4H8H)	27,2
Colour consistency in MacAdam steps SDCM	≤5
Photobioligical risk	RG0

Electrical data

V
2





IP44 Diffuser Downlight LED Downlight D1 TU 6 IP44 18W 830 S 93109216


Logistic data

Box quantity	1
Shipment	Standard
Product status	Available

Light distribution







Downloads & Links

Go to the catalog site (HTTP)

Datasheet (PDF)

Installation guide (PDF)

Images (HTTP)

DoC Document (PDF)

Datasheet (HUN) (PDF)