

# ATS1235

## 16 to 32 zones Gen2 868AM wireless receiver including plastic housing

### Product overview

The ATS1235 Advanced Wireless Data Gathering Panel (DGP) receiver adds wireless capabilities to the Advisor Advanced & Master panels using Aritech 868 MHz Gen 2 Wireless Sensors: i.e. PIR, Glassbreak etc. Maximum distance from the panel is 1500 m.

The ATS1235 features spatial diversity to minimize wireless signal nulls or dead spots and has a nominal open-air receiving range of 400 m. If dead spots need to be eliminated, a 868 MHz repeater may be used. It can be powered from the control panel databus or a remote auxiliary power supply.

Fob buttons may be programmed for users to arm and disarm or to control relays.

With ATS1235 Advanced wireless expanders, the control panel becomes a hybrid system where one can optimize the system by distributing receivers in the premises.

The ATS1235 is EN50131 Grade 2 approved.

### Expanders

Expanders are used to expand the number of alarm inputs in an Advisor Advanced system. Expanders allow inputs and outputs/relays to be connected at a location remote from an Advisor Advanced panel. Expanders communicate via poll & reply messages. Detectors, door contacts and other detection devices are connected to expanders that report any change of state to the control panel for processing. Available expanders include support for conventional devices, wireless devices as well as intelligent addressable devices. A special expander is available providing expansion of four to eight intelligent doors or lifts.

Up to 15 or 30 expanders can be connected to an Advisor Advanced depending on the variant.

### System databus connection

The system databus is used to connect expanders as well as keypads and readers (RASs) to the Advisor Advanced control panel. Remote devices can be up to 1.5 km from a control panels when using the preferred wiring and cable types. Keypads, readers and expanders have to be connected via a 2 pair twisted and shielded data cable to the system databus connection to achieve this. (WCAT52 is recommended). Daisy chain is the preferred wiring method. The shield of the data cable should be connected to earth at the control panel and should be left disconnected at any other end.

If a failure in communication occurs, the expander remembers the last alarm in a system preventing loss of an alarm due to a short interruption in data communication.



### Details

- Expands the Advisor Advanced panel with 32 wireless zones
- 868 MHz Wireless GEN2 Sensors
- Quick configuration using the Aritech "Learn Mode" technology
- Located up to 1500 m from the Advisor Master panel using WCAT52/54 cable
- Features spatial diversity to minimize wireless dead spots and has a nominal open-air receiving range of 460 m
- Use the Aritech 868 MHz repeater to improve range
- Powered from the control panel databus or a remote auxiliary power supply
- Fob buttons may be programmed for users to arm and disarm or to control relays
- To remotely open and close a garage door as well as arm or disarm an office security system

# ATS1235

## 16 to 32 zones Gen2 868AM wireless receiver including plastic housing

### Technical specifications

---

#### General

Expander type	Wireless expander
Product line	Advisor Advanced, ATS Master
Connection type	Databus connection
Compatibility	868 MHz Gen2 sensors, ATS Advanced FW v017.017.0067 or higher, ATS Master FW v04.09.16 or higher
Max. distance from panel	1.5 km
Max. per panel	15 / 30 (depending on panel type)
Specified cable	WCAT52 / WCAT54 or equivalent

#### System

Addressing	DIP Switches
------------	--------------

#### Inputs

Total	32
No. of wireless zones	32 (16 wireless keyfobs)

#### Wireless

Operating frequency	868 MHz AM
Wireless open-air range	400 m

#### Electrical

Operating voltage	9.5 to 14.4 VDC
Current consumption	77 mA
Integrated power supply	No

#### Physical

Physical dimensions	165 x 115 x 40 mm
Net weight	350 g

#### Environmental

Operating temperature	-10 to +55°C
Relative humidity	95% noncondensing
Environment	EN50130-5 ; Class II - Indoor (General)

#### Standards & regulation

Compliancy	CE
Certification	CE, EN50131 Grade 2



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 17 November 2021 - 15:26