Safe-Torque torque wrenches












EAN: 4013288223005 **Size:** 275x140x65 mm

Part number:05075830001Weight:1023 gArticle number:Safe-Torque A 1 Set 1Country of origin:CZ

Customs tariff 82079030

number:



- Torque Lock function: The torque function can be deactivated and the tool can then be used as a standard ratchet with high loosening moments and for applications with defined angles of rotation
- For controlled clockwise and counterclockwise torque operation tightening and loosening with or without torque
- Easy setting and saving of the desired torque value with audible and tactile clicks when reaching the scale values
- After the target torque has been reached, the release angle is only 30°
- The fine toothing with 72 teeth allows for a low return angle of 5°
- 1/4" square head drive with socket locking

10-piece 1/4" torque wrench set in a robust textile box; torque wrench with slide-over mechanism. Once the set torque has been reached, the tool cannot be overtightened, so that excessive torque cannot be applied. Setting range of 2 to 12 Nm for controlled clockwise and counterclockwise torque operation. Easy setting and saving of the default value: The audible and tactile clicks on reaching the scale values facilitate the safe setting of the desired torque value. The Torque Lock function allows use as a standard ratchet without torque function. Thus also usable for applications with angles of rotation. Max. breaking torque of the ½" square head as per DIN 3122. The return angle of only 5° allows the ratchet to be used even in confined spaces. Included are: Safe-Torque A 1 torque wrench, 1/4" square head, 2-12 Nm, 8 sockets with 1/4" drive and one short extension.























Safe-Torque torque wrenches





Safe-Torque

Easy torque setting

Easy setting and saving of the

required torque with audible and

tactile clicks on reaching the scale

Slide-over mechanism prevents application of excessive torques



The Safe-Torque A 1 torque wrench is equipped with a slideover mechanism. Once the set torque value has been reached, the tool cannot be overtightened, so that excessive torque cannot be applied.

Low return angle



The fine-toothed Safe-Torque torque wrench with 72 teeth has a back-pivoting angle of only 5°. The small stroke offers quick and precise working in all installation positions.

Torque Lock function



The torque function can be deactivated. The Safe-Torque torque wrench can then also be used as a standard ratchet with high loosening moments and for applications with defined angles of rotation.

For 1/4" sockets



The Safe-Torque A 1 torque wrench has 1/4" square head mounting and is suitable for 1/4" sockets.

For clockwise and counterclockwise operation



The Safe-Torque torque wrench is suitable for clockwise and counterclockwise operation with a set torque. When the Torque Lock function is deactivated, tightening and loosening is enabled without torque.

Space for more tools



The Wera Belts can be attached to the hook and loop fastener strips in the textile box of the sets Safe-Torque A 1 Set 1 and Safe-Torque A 1 Imperial Set 1, so more sockets and/or bit sockets can be stored and transported.

Web link

values.

https://products.wera.de/en/torque_tools_safe-torque_torque_wrenches_and_accessories_safe-torque_torque_wrenches_safe-torque_a_1_set_1.html

Safe-Torque A 1 Set 1, 1/4" square head drive, 2-12 Nm, 10 pieces

Safe-Torque torque wrenches



Set contents:

Safe-Torque A 1 torque wrench with 1/4" square head drive, 2-12 Nm, 1/4" x 2-12 Nm

05075800001 1x 1/4" x 2-12 Nm



8790 HMA Zyklop 1/4" socket, 5.5 x 23 mm



| 05003504001 | 1x | 5.5 x 23 mm |
|-------------|----|-------------|
| 05003505001 | 1x | 6 x 23 mm |
| 05003506001 | 1x | 7 x 23 mm |
| 05003507001 | 1x | 8 x 23 mm |
| 05003509001 | 1x | 10 x 23 mm |
| 05003510001 | 1x | 11 x 23 mm |
| 05003511001 | 1x | 12 x 23 mm |
| 05003512001 | 1x | 13 x 23 mm |

8794 SA Zyklop extension with free-turning sleeve, short, 1/4", 1/4" x 75 mm

05003525001 1x 1/4" x 75 mm



Hook and Loop Fastener Strip 240, 50 x 240 mm

1x 50 x 240 mm

