

connection terminal plate, 3-pole (01199000)



The picture may show a similar product.

Description

Part No.: **01199 000**

CRITO 60Classic

connection terminal plate, 3-pole

95 - 185 mm²

for busbars 20, 25, 30 x 5, 10 and section busbars

System

60Classic

Advantages of the product

Terminals with captive clamping screws

Conductor can be overlapped

Indication of nominal cross-section and tightening torque noted on the terminals.

Product group 07

Subgroup 48

pack size 1

EAN 4021267011994

ECLASS 14.0 27250116
ETIM 5.0 EC000001
ETIM 8.0 EC000001
ETIM 10.0 EC000001

Approvals

Standards

IEC 61439-1:2020
IEC 60999-1:1999
IEC 60999-2:2003

Approvals

DNV GL



EAC Type: TE-3P

CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2020
IEC 60999-1:1999
IEC 60999-2:2003

Electrical data IEC

rated current (IEC): 350 A
rated voltage (IEC) AC: 690 V

rated peak withstand current I_{pk} max.: 55.8 kA

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

max. permitted voltage (IEC) AC: 1000 V
max. permitted voltage (IEC) DC: 1500 V
current capacity (IEC) max. of the terminal: 460 A

min. permitted operation temperature -40°C

Mechanical data

W x H x D: 135 x 200 x 118
weight: 132.2 kg/100
poles: 3-pole
for busbars: 20, 25, 30 x 5, 10 and section busbars

Terminal points

min. cross-section: 95 mm²
max. cross-section: 185 mm²
Suitable for aluminium cables.
When using aluminium cables, observe the maintenance instructions.

für Anwendungen nach IEC / EN :
Cu und Al 95 - 185 mm² Rundleiter mehrdrähtig und Sektorleiter mehrdrähtig
Cu auch feindrähtig, direkt geklemmt

for applications acc. to IEC / EN:
Cu or Al 95 - 185mm², round stranded or sector-shaped stranded cables
also fine stranded Cu cables (direct clamping)

Material properties

halogen-free: Yes

Application notes

Suitable for aluminium cables.
When using aluminium cables, observe the maintenance instructions.
The insulation performance of the article depends on the installation conditions.

<https://pim.woehner.de/EN/EN/1000046317>