

MANUFACTURER'S DECLARATION OF CONFORMITY

<i>No.</i>	EX.081-2023
<i>Issuer's name:</i>	GEWISS S.p.A.
<i>Issuer's address:</i>	Via A. Volta, 1 24069 Cenate Sotto (BG) ITALY
<i>Object of the declaration:</i>	FK9 range Type References: see Annex 1

We declare that the products mentioned above have been tested according to the A method test – cycle one set out by the following international Standard:

Document No.	Title	Date of issue
ISO 4892-2	<i>Plastics - Methods of exposure to laboratory light sources Part 2: Xenon-arc lamps Method A cycle 1</i>	3rd Ed. 2013

After 500 hours of external exposition simulation (Xenotest Beta+ – Atlas), there is no noticeable change of the colour on the products and there are not superficial creases.


Signed for and on behalf of:

GEWISS S.p.A.

Place and Date:

Cenate Sotto, 05th June 2023

MATTEO GAVAZZENI
Corporate Industrial Property, Quality
and Product Certification Director



Annex 1:

List of the Type References subject of the Declaration No. EX.081-2023

FK9 RANGE – LIGHT PLIABLE CONDUIT	
TYPE REFERENCE	DESCRIPTION
DX10016R	FK 9/16 GREY RAL7035 LIGHT PLIA. CONDUIT
DX10016R10	FK9/16 GREY LIGHT PLIABLE CONDUIT L=10M
DX10016R25	FK9/16 GREY LIGHT PLIABLE CONDUIT L=25M
DX10016R50	FK9/16 GREY LIGHT PLIABLE CONDUIT L=50M
DX10020R	FK 9/20 GREY RAL7035 LIGHT PLIA. CONDUIT
DX10020R10	FK9/20 GREY LIGHT PLIABLE CONDUIT L=10M
DX10020R25	FK9/20 GREY LIGHT PLIABLE CONDUIT L=25M
DX10020R50	FK9/20 GREY LIGHT PLIABLE CONDUIT L=50M
DX10025R	FK 9/25 GREY RAL7035 LIGHT PLIA. CONDUIT
DX10025R10	FK9/25 GREY LIGHT PLIABLE CONDUIT L=10M
DX10025R25	FK9/25 GREY LIGHT PLIABLE CONDUIT L=25M
DX10025R50	FK9/25 GREY LIGHT PLIABLE CONDUIT L=50M
DX10032R	FK 9/32 GREY RAL7035 LIGHT PLIA. CONDUIT
DX10032R10	FK9/32 GREY LIGHT PLIABLE CONDUIT L=10M
DX10032R25	FK9/32 GREY LIGHT PLIABLE CONDUIT L=25M
DX10040R	FK 9/40 GREY RAL7035 LIGHT PLIA. CONDUIT
DX10050R	FK 9/50 GREY RAL7035 LIGHT PLIA. CONDUIT
DX10116R	FK 9/16F GREY LIGHT PLIABLE CONDUIT W/P
DX10120R	FK 9/20F GREY LIGHT PLIABLE CONDUIT W/P
DX10125R	FK 9/25F GREY LIGHT PLIABLE CONDUIT W/P
DX10132R	FK 9/32F GREY LIGHT PLIABLE CONDUIT W/P
DX10140R	FK 9/40F GREY LIGHT PLIABLE CONDUIT W/P
DX10150R	FK 9/50F GREY LIGHT PLIABLE CONDUIT W/P