



PRODUCT MANAGEMENT TEAM



70210520

DAMPPROOF SLIM Eco Class

DAMPPROOF SLIM Eco Class



+ Portfolio

18 W	36 W	48 W
600 mm	1200 mm	1500 mm
1980 lm	4320 lm	5520 lm
4000K	6500K	



+ USP

30000 L70
2Y GUARANTEE™
IP65

DAMPPROOF SLIM Eco Class

DAMPPROOF SLIM Eco Class



High ingress protection IP65

No yellowing thanks to high quality polycarbonate housing



Luminous efficacy: up to 120lm/W

Long lifespan
L70 - 30.000h

Easy and quick installation with flexible slideable aluminium mounting brackets

DP SLIM ECO



**DAMPPROOF
SLIM
Eco Class**



Model	EAN10	Wattage [W]	Lumen [lm]	Efficiency [lm/W]	Electric isolation class	Light Distribution/ Beam angle [°]	Lifetime (LXX @ YY°C)	Product dimensions [mm]	Protection class (IP)	IK level	Ambient Operating Temperature [°C]	Warranty [yrs]	Included accessory
DP SLIM ECO 600 18W 840 IP65 GY	4058075601574	18	1980	110	II	110	30.000 (L70B50 @ 25°C)	600x60x35	IP65	IK03	-20° .. +40°	2	Mounitng screws, stainless steel brackets
DP SLIM ECO 600 18W 865 IP65 GY	4058075601598	18	1980	110	II	110	30.000 (L70B50 @ 25°C)	600x60x35	IP65	IK03	-20° .. +40°	2	Mounitng screws, stainless steel brackets
DP SLIM ECO 1200 36W 840 IP65 GY	4058075601611	36	4320	120	II	110	30.000 (L70B50 @ 25°C)	1200x60x35	IP65	IK03	-20° .. +40°	2	Mounitng screws, stainless steel brackets
DP SLIM ECO 1200 36W 865 IP65 GY	4058075601635	36	4320	120	II	110	30.000 (L70B50 @ 25°C)	1200x60x35	IP65	IK03	-20° .. +40°	2	Mounitng screws, stainless steel brackets
DP SLIM ECO 1500 48W 840 IP65 GY	4058075601659	48	5520	115	II	110	30.000 (L70B50 @ 25°C)	1500x60x35	IP65	IK03	-20° .. +40°	2	Mounitng screws, stainless steel brackets
DP SLIM ECO 1500 48W 865 IP65 GY	4058075601673	48	5520	115	II	110	30.000 (L70B50 @ 25°C)	1500x60x35	IP65	IK03	-20° .. +40°	2	Mounitng screws, stainless steel brackets