


PE/N-support (01489)



The picture may show a similar product.

Description

Part No.: **01489** 000

PE/N-support

1-pole, attachable to 01500 or separate mounting
for busbars 12, 15, 20, 25, 30 x 5, 10

System

60Classic

Product group 06

Subgroup 03

pack size 10

EAN 4021267014896

ECLASS 6.1 27400607

ECLASS 7.1 27400607

ETIM 4.0 EC001166

ETIM 5.0 EC001166

Approvals

Standards

IEC 61439-1:2020

UL 508

Approvals

CSA , UL



type number: 489

UL file: E123577, UL category (for USA): NMTR2 <https://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR8 <https://www.ul.com>

CSA file: 110285, CSA class: 3211-37 <https://directories.csa-international.org>

CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2020

Electrical data IEC

rated voltage (IEC) AC: 690 V

rated isolation voltage U_i AC: 1000 V

rated surge voltage U_{imp} : 6 kV

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 0.0 W.

(The power dissipation at full load would be 0.0 W.)

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

max. permitted voltage (IEC) AC: 1000 V
max. permitted voltage (IEC) DC: 1500 V

Details UL

Standards

UL 508

Electrical data UL

rated voltage (UL) AC: 600 V
rated frequency (UL): 50 / 60 Hz

Mechanical data


W x H x D: 26 x 63 x 51
weight: 5.9 kg/100
poles: 1-pole
for busbars: 12, 15, 20, 25, 30 x 5, 10

Application notes


Can be mounted individually or together with a 3-pole busbar support
can also be used as a centre support.

Accessories


further accessories



78442 000
label
PE green-yellow
diameter 15 mm



78443 000
label
N blue
diameter 15 mm



78447 000
label
PE/N green-yellow / blue
diameter 15 mm

<https://pim.woehner.de/EN/INT/1000043805>