



# 6630CM-N

## 360° - FRESNEL DUAL

### DesignLine Series- Dual Technology

---

A range of Dual Technology motion sensors is added to this product line intended for use in residential and light commercial environments. The DesignLine series builds customer value by meeting customers' security needs while respecting budget constraints. This range is quick to install and comes with a stylish housing.

It provides detection for a variety of ranges, including up to 360 degrees of coverage for ceiling mount applications and an EN Grade III certified variant with the AntiMasking functionality on board. It even has a variant with smart pet immunity up to 35kg, making this series all the more attractive.

These motion sensors deliver easy solutions for installers : being equipped with 2 standard EOL resistor values, providing flexibility in installing height and a separate walktest input line.



### Details

---

- 360° coverage up to 9.3m at 3.6m mounting height
- Wifi immune microwave technology
- Digital signal processing
- Unique stylish design
- Quick to install
- Built-in EOL resistor values
- EN50131 Grade 2
- Holds several European security approvals

# 6630CM-N

## 360° - FRESNEL DUAL

### Technical specifications

---

#### General

Technology	Dual
Anti masking	No
Pet immune	No
Camera	No

#### Detection

Max. detection range	9 m
Microwave frequency (nom.)	24 GHz
Undercrawl protection	Yes
Target speed range	0.3 to 3.0 m/s

#### Wired / wireless

Wired-wireless	Wired
----------------	-------

#### Inputs / outputs

Alarm relay characteristic	<24 VDC, 50mA, NC
Tamper relay characteristic	<24 VDC, 50mA, NC
Relay configuration	Multiple EOL values

#### Electrical

Operating voltage	9 to 15 VDC
Current consumption	21 mA (nominal)

#### Physical

Physical dimensions	116 x 33 mm (Ø x H)
Net weight	110 g
Colour	White

#### Environmental

Operating temperature	-10 to 55 °C
Relative humidity	max 95%
Environment	Indoor

#### Regulatory

EN50131 grade	Grade 2
---------------	---------

#### Used technology

	PIR and 24Ghz microwave
--	-------------------------

#### Max. detection range

	coverage diameter of 9.3m at 3.6m mounting height
--	---

#### Optics

	Fresnel lens
--	--------------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 16 May 2022 - 14:08