



Led Panel RTI

PAN RTI M600 25W U19C90 ED4K

Order code 40151

EAN 8002219757883

Technical specifications

Absorbed Power	24 W
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-20 °C
Ambient temperature (max)	40 °C
Insulation class	I
CCT light tone	4000 K
Optical protection grade	IP40
LED number	104
Photobiological risk	RG0
Colour consistency	SDCM3
CRI color rendering	>90
Driver type	ED
Ballast	For constant current LED
Efficiency	142 lm/W
Energy class	D
Equivalent power	4x18w
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Glow wire strength	960 °C - 30s.
Luminaire flux	3400 lm
Luminous flux L80B20	100000 h
UGR	19
Voltage supply range (max)	253 V
Voltage supply range (min)	207 V





Installation and applications

Environment	Offices
Application	Offices, Commercial Areas, Public Areas, Didactic Areas

Mechanical specifications

Height	34 mm
Length	595 mm
Width	595 mm
Weight	1.9 Kg
Body material	Sheet steel epoxy coated
Colour housing	White RAL 9003
Lens material	PMMA transparent thermoplastic
Box protection grade	IP20



Protection grade IP	IP20/IP40
Protection grade IK	IK05

Certifications and norms

UK SI 2021 No. 1095, EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019, EN 61547:2009, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-2:2012, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013


Accessories



70100
SUSPENSION 4 HOOK
PANELED



70059
KIT CAVETTO DI SICUREZZA



20089
CORNICE PLAF BACKLITE
600X600



40190
STAFFA ALTA PAN RTI 600



70039
KIT CONTROLLO SOFFITTO PAN
RTI

Inverter accessories



19367
INV P&L LED SE/SA 1H 60-180V



19371
INV P&L LED SE/SA 3H 60-180V