



EcoLED T8 Tuttovetro

ETUBE LED T8 1500MM 24WG13 840



The tube is designed to achieve maximum luminous efficiency and to be used inside existing luminaires, replacing traditional T8 fluorescent tubes. It is protected by a special plastic casing capable of retaining fragments in case of breakage, and is therefore suitable for HACCP installations.



Order code 56219

EAN 8002219717535

Technical specifications

Absorbed Power	24 W
Lampholder	G13
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-20 °C
Ambient temperature (max)	40 °C
CCT light tone	4000 K
Photobiological risk	RG0
Beam angle	160 °
Bulb shape	Other
Colour consistency	SDCM6
Consumption (1000h)	24 kWh
CRI color rendering	>80
Diameter	28 mm
Efficiency	112 lm/W
Energy class	E
Epel code	562933
Equivalent power	58W
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Power factor	0.91
Life	20000 h
Lighting Sources Flux	2700 lm
Luminous flux L70B50	15000 h
Switching cycles	8000
Voltage supply range (max)	240 V
Voltage supply range (min)	220 V


Mechanical specifications

Height	1513 mm
Diffuser finiture	Frosted
Protection grade IP	IP20

Certifications and norms

UK SI 2021 No. 1095, EN IEC 55015:2019
+ A11:2020, EN IEC 61000-3-2 :2019, EN
61547:2009, EN 62471:2008, EN
62776:2015, EN IEC 63000:2018, EN
62493:2010, EN 61000-3-3:2013, REG.
2019/2020(EU)

Accessories





15081
MODULO TUBI LED