



# X-Six LED - CCT

## X-SIX DWL LED CCT REG 18W

Order code **71062**

EAN 8002219754875

### Technical specifications

Absorbed Power	<b>18 W</b>
Supply voltage type	<b>AC</b>
Nominal voltage (AC)	<b>230 Vac</b>
Ambient temperature (min)	<b>-20 °C</b>
Ambient temperature (max)	<b>40 °C</b>
Insulation class	<b>II</b>
CCT light tone	<b>3000 K, 4000 K, 6000 K</b>
CCT (max)	<b>6000 K</b>
CCT (min)	<b>3000 K</b>
LED number	<b>96</b>
Beam angle	<b>120 °</b>
Colour consistency	<b>SDCM3</b>
CRI color rendering	<b>&gt;80</b>
Diameter	<b>225 mm</b>
Ballast	<b>For constant current LED</b>
Efficiency	<b>80 lm/W</b>
Frequency (max)	<b>60 Hz</b>
Frequency (min)	<b>50 Hz</b>
Power factor	<b>0.55</b>
Glow wire strength	<b>550 °C - 30s.</b>
MTBF driver	<b>30000 h</b>
Luminaire flux	<b>1440 lm</b>
Mounting	<b>Ceiling, Recessed</b>
Voltage supply range (max)	<b>253 V</b>
Voltage supply range (min)	<b>207 V</b>



### Installation and applications


Environment	<b>Offices</b>
Application	<b>Offices, Condos, Hotels, Malls, Shops</b>

### Mechanical specifications

Height	<b>20 mm</b>
Weight	<b>0.4 Kg</b>
Colour housing	<b>White</b>
Protection grade IP	<b>IP20</b>
Protection grade IK	<b>IK05</b>

### Certifications and norms

UK SI 2021 No. 1095, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-2:2012, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013, REG. 2019/2020(EU), EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019



Foro di incasso Ø 65/210 mm

