

ECICTA16TBL

HF ICTA PLIABLE PP CONDUIT 34223 Ø16 mm - 100 m WITH DRAW TAPE - BLUE



IMMAGINE
RAPPRESENTATIVA

EC

REPRESENTATIVE
IMAGE

Conduits and fittings > Conduits > Corrugated conduits >
Series icta - pp - class 34223 - 750 n > plastic conduits > Black
- cable puller

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

| | | | | | |
|---|----------------------------|--|---------------------------|--|--------------------------|
| Flush-mounted installation | Yes | Material | Polypropylene (PP) | Halogen free | Yes |
| Colour | Blue | RAL-number | 5005 | UV resistant | No |
| Suitable for underground installation | No | Operating temperature | -5-90 °C | Bending strength | Pliable, self recovering |
| Compressive strength class according to EN 61386-1 | Medium (class 3 / 2 Joule) | Impact strength class according to EN 61386-1 | Heavy (class 4 / 6 Joule) | With sleeve | No |
| Fire retardant version | Yes | Surface mounting | No | Suitable for installation on wood | Yes |
| Suitable for hollow wall installation | Yes | Suitable for concrete installation | Yes | Machine and systems installation | No |
| Suitable for underfloor installation (screed) | Yes | Suitable for outdoor installation | No | Inner diameter | 10.8 mm |
| Outer diameter | 16 mm | High conducting inner coating | Yes | With metre indication | No |

Technical Characteristics

Lunghezza Bobina 100 m

Documentation available for download




Certification
Test Report ICTA
Contenuto alogeni
MI23-0092109-01.pdf



Brochure
BROCHURE TUBI
doppie.pdf

Barcode



8059307211086
Cardboard
100 MT
5.11 [kg]



8059307211277
Pallet
7000 MT
357.7 [kg]