

NEPTUN24 EU



SM Damp area distributor IP65, NEPTUN24 EU, PS, closed ventilation

Product No.: 7270010
Type: NEPTUN24 EU

- NEPTUN - Seeks the challenge. Masters every situation.
- Protects installations against harmful ingress of water and dust - IP65
 - Tool-free cable entry thanks to IP65 membrane entry flange
 - Tool-free adjustable top-hat rail thanks to click system
 - Rugged housing for harsh conditions
 - 1- to 4-row variants
- * Rated insulation voltage of 1000 V AC / 1500 V DC only applicable when using the external mounting brackets (7290197)
- Article not available in the following countries: DE, AT, CH, LU

Measures	
Height	465 mm
Width	310 mm
Depth	150 mm

Material	
Housing material	PS
Door material	PC

Environmental conditions	
Ambient temperature (minimum)	-25 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (24h)	35 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Accessories	
Equipped with	1x PE-N screw terminal (KN17PE) 1x cover strip (ADS12gr)

Technical features

Design voltage	AC 400V / AC 1000V / DC 1500V * V
Design current	63 A
Total inserts	28x Ø 5-12 mm 14x Ø 5-15 mm 8x Ø 6-20 mm 2x Ø 8-26 mm 2x M32/M50 2x M20 4x M25

Properties

Installation type	SM
Colour	grey
Degree of protection (IP)	IP65
Insulation	Protection class II
Impact resistance	IK08
Number of rows	2
Number of compartments	24
Can be lead sealed	true
Halogen-free	true

Certificates & Standards

VDE	true
CE	true
Glow wire test	650 °C
REACH	false
RoHS	true

Note

Note	Not suitable for outdoor installation
------	---------------------------------------