



FM Device connection socket E1072K

Order number: 7320028

Type: E1072K

Efficiency in energy and handling

- Maximum airtightness thanks to new f5 membrane (tear-resistant, flexible, airtight, pre-embossed, tool-free)
- Increase of energy efficiency in buildings
- More comfort by avoiding draughts
- Easy to install
- Easy to use without additional tools
- Guaranteed compliance with the standard distance

Dimensions

| | |
|----------|------------|
| Depth | 65 - 65 mm |
| Diameter | 60 mm |

Environmental conditions

| | |
|---|--------|
| Ambient temperature (24h) | 35 °C |
| Ambient temperature (maximum) | 40 °C |
| Ambient temperature (minimum) | -25 °C |
| Max. rel. humidity at 25°C (short term) | 90 % |
| Max. rel. humidity at 40°C | 50 % |

Material

| | |
|-----------------|--------|
| Socket material | PP/TPE |
|-----------------|--------|

Properties

| | |
|---------------------------|-------|
| Can be lead sealed | - |
| Colour | Black |
| Degree of protection (IP) | IP30 |
| Free of heavy metals | true |
| Halogen-free | true |
| Installation type | FM |
| PVC-free | true |
| Silicone-free | true |
| Stackable | true |
| Weather-resistant | - |

Technical features

| | |
|--------------------|---------------------|
| Cable entry | 6 |
| Design voltage | 400 V |
| max. cross section | 2,5 mm ² |
| Pipe entry M20/M25 | 2/4 |

Certificates & standards

| | |
|----------------|---|
| CE | true |
| Glow wire test | 650 °C |
| REACH | true |
| RoHS | true |
| Standards | <ul style="list-style-type: none"> DIN EN 60670-1(VDE 0606-1) DIN EN 60670-22 (VDE 0606-22) |
| VDE | true |

Accessories

| | |
|---------------|------|
| Equipped with | None |
|---------------|------|