


Surface mounted light fittings for T5 lamps



LLX228ALDP



LLX T5

Body:

White painted (RAL 9003) metal sheet

Optic (&):

ALDP - double parabolic louvre category C2 of highly polished aluminium

MATDP - double parabolic louvre category C2 of mat aluminium

AL - parabolic louvre of highly polished aluminium with mat aluminium cross blades

B - white parabolic louvre

Wiring (#):

EP - high frequency ballast HFB (standard)

EPSA - HFB analogue dimmable (1-10 V)

EPSD - HFB digital dimmable TRIDONIC ECO

EPSDD - HFB digital dimmable DALI

MULTIWATT - universal HFB for T5 lamps

Application:

These light fittings can be used as surface mounted or suspended.

Accessories:

Tube suspension

Cord suspension ZH22

Protection grid OM

Versions (@):

NZ - emergency pack

OK - double-circuit wiring

RAL9006 - surface finished in RAL 9006

Note:

Surface mounted style of installation is recommended. When light fittings are suspended, they should be hung by 4 cords or tubes.

| | W | A | B | X | Y | kg |
|---------------------|---------------|------|-----|------|-----|-----|
| LLX114 (24) &#@ | 1x14 (24) | 610 | 153 | 300 | - | 1,7 |
| LLX214 (24) &#@ | 2x14 (24) | 610 | 238 | 300 | 150 | 2,6 |
| LLX414 (24) &#@ | 4x14 (24) | 610 | 410 | 300 | 330 | 3,4 |
| LLX128 (54) &#@ | 1x28 (54) | 1210 | 153 | 900 | - | 3,0 |
| LLX228 (54) &#@ | 2x28 (54) | 1210 | 238 | 900 | 150 | 4,0 |
| LLX328 (54) &#@ | 3x28(54) | 1210 | 324 | 900 | 235 | 5,0 |
| LLX135 (49, 80) &#@ | 1x35 (49, 80) | 1510 | 153 | 1200 | - | 4,0 |
| LLX235 (49, 80) &#@ | 2x35 (49, 80) | 1510 | 238 | 1200 | 150 | 5,5 |

