



## LED street light fitting

**MODUS LVX, MidPower LED, 3000lm, 4000K, low opal cover, nondimmable, straight flange diam. 60**

**Code:** LVX3000NO4V1/NDV60  
**EAN:** 8595073710113

This product contains a light source with energy efficiency class C



### Luminaire properties

Product category:	<b>Luminaire for streets and places</b>	Effective luminous flux (lm):	<b>3200</b>
System power (W):	<b>32</b>	Luminaire efficacy (lm/W):	<b>100</b>
Rated lifetime L70/B50 (h):	<b>40000</b>	Degree of protection (IP):	<b>IP65</b>
Mounting method:	<b>Side-entry</b>	Color housing:	<b>Grey</b>
Impact strength:	<b>IK08</b>		
Material housing:	<b>Plastic</b>		
With connection cable:	<b>Yes</b>	Light source included:	<b>Yes</b>
Made in Czech republic:	<b>Yes</b>		

### Light source

Light source type:	<b>LED</b>	Color temperature (K):	<b>4000</b>
Color rendering index CRI:	<b>80-89</b>	Replaceability:	<b>Replaceable light source by professional, replaceable ballast</b>
Light source type:	<b>1990440184006</b>	Energy efficiency class:	<b>C</b>

### Optical system

Optical system:	<b>PCO</b>	Material cover:	<b>Plastic, opal</b>
-----------------	------------	-----------------	----------------------

## Dimensions

Length (mm):	<b>752</b>	Width (mm):	<b>180</b>
Height/depth (mm):	<b>162</b>	Cable length (m):	<b>0,2</b>
Suitable for top end size (mm):	<b>60</b>	Size version:	<b>XM</b>
Weight (kg):	<b>3,8</b>		

## Electrical values

Protection class:	<b>I</b>	Voltage type:	<b>AC</b>
Type of control gear:	<b>LED operating device current-controlled</b>	Nominal voltage (V):	<b>220...240</b>
Control gear included:	<b>Yes</b>	Type of wiring:	<b>Ending</b>
No dim function:	<b>Yes</b>		