



LED street light fitting

MODUS UL9000, AL body, LED 750, 3DIM

Code: UL9000V15/3DIM

EAN: 8595073711592

This product contains a light source with energy efficiency class C



Luminaire properties

Product category:	Luminaire for streets and places	Effective luminous flux (lm):	11200
System power (W):	87	Luminaire efficacy (lm/W):	129
Rated lifetime L70/B50 (h):	100000	Degree of protection (IP):	IP65
Mounting method:	Post-top/side-entry	Color housing:	Grey
Surface protection:	Powder coating		
Material housing:	Aluminium		
With connection cable:	Yes	Light source included:	Yes
Made in Czech republic:	Yes		

Light source

Light source type:	LED	Color temperature (K):	5000
Color rendering index CRI:	70-79	Replaceability:	Removeable light source, replaceable ballast
Light source type:	1990480175003	Energy efficiency class:	C

Optical system

Optical system:	LENS	Material cover:	Glass transparent
Adjustable optics:	No		

Dimensions

Length (mm):	650	Width (mm):	240
Height/depth (mm):	71	Cable length (m):	0,2
Suitable for top end size (mm):	60	Size version:	S
Weight (kg):	7		

Electrical values

Protection class:	I	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220...240
Control gear included:	Yes	Type of wiring:	Ending
Dimming DALI:	Yes	Dimming LineSwitch:	Yes
MODUS SMART:	Astro Dim		