

# LS/PD DALI LI UF

LS/PD DALI LI UF | Sensors for light management systems

### Areas of application

- Installation in industry and office luminaires



### Product family benefits


- Extremely low profile
- Presence detection range can be restricted by snap on shutters

### Product family features

- Direct connection to DALI
- Light and presence sensor for luminaire installation
- Presence detection via passive IR element
- Light sensor working range: 10...1000 lx (measured at sensor)
- Function indication via integrated LED
- Mounting height: 2...4 m

### Technical data

## Dimensions & weight



Length	50.0 mm
Width	21.0 mm
Height	16.0 mm
Product weight	10.00 g

### Colors & materials

Product color	White
---------------	-------

### Temperatures & operating conditions

## Capabilities

Dimmable	No	
Dimming interface	DALI	
Maximum installation height	4 m	
Detection area	36 m <sup>1)</sup>	
Detection angle	90 °	
Operating range, light sensor	01000 lx	
Number of control outputs	2	
Type of installation	Luminaire integration	

<sup>1)</sup> Maximum diameter

## **Certificates & standards**

Type of protection	IP20
--------------------	------

### Logistical data

### Product datasheet

Commodity code	853710989900

#### Download Data

	File
大	User instruction LS PD DALI LI UF Sensor mounting instruction
<b>龙</b>	User instruction LS PD DALI LI UF Sensor User Instruction
7	Declarations of conformity Declaration of conformity UF Sensors

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899984608	LS/PD DALI LI UF	Shipping carton box 10	390 mm x 95 mm x 75 mm	2.78 dm <sup>3</sup>	253.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.