

# PRODUCT DATASHEET

## ST8V-EM 7.6 W/4000 K 600 mm EM

SubstiTUBE Value | Economic LED tubes for electromagnetic control gears



---

### AREAS OF APPLICATION

- General illumination within ambient temperatures from -20...+45 °C
- Corridors, stairways, parking garages
- Cooling and storage rooms
- Domestic applications
- Industry
- Warehouses
- Supermarkets and department stores

---

### PRODUCT BENEFITS

- No bending thanks to glass technology
- Quick, simple and safe replacement without rewiring
- Energy savings of up to 65 % (compared to T8 fluorescent lamp on CCG)
- Instant-on light, therefore ideally suitable in combination with sensor technology
- Very high resistance to switching loads
- Also suitable for operation at low temperatures

---

### PRODUCT FEATURES

- LED alternative to classic T8 fluorescent lamps in CCG luminaires
- Uniform illumination
- Mercury-free and RoHS compliant
- Luminous efficacy: up to 105 lm/W
- Tube made of glass



## TECHNICAL DATA

### Electrical data

Nominal wattage	7.60 W
Rated wattage	7.60 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz
Nominal current	0.035 A
Type of current	AC
Power factor $\lambda$	> 0.90

### Photometrical data

Light color (designation)	Cool White
Rated color temperature	4000 K
Nominal luminous flux	800 lm
Rated luminous flux	800 lm
Color rendering index Ra	$\geq 80$
Lumen main.fact.at end of nom.life time	0.70
Color temperature	4000 K
Luminous flux	800 lm
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 6$ sdc

### Light technical data

Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s
Rated beam angle (half peak value)	210.00 °

### Dimensions & weight



Length with base excl. base pins/connection	590.00 mm
---	-----------

<b>Tube diameter</b>	25.6 mm
<b>Base diameter</b>	25.5 mm
<b>Product weight</b>	100.00 g
<b>Overall length</b>	603.0 mm

#### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+45 °C
----------------------------------	--------------

#### Lifespan

<b>Nominal lamp life time</b>	30000 h
<b>Rated lamp life time</b>	30000 h
<b>Number of switching cycles</b>	200000

#### Additional product data

<b>Base (standard designation)</b>	G13
<b>Mercury-free</b>	Yes

#### Capabilities

<b>Dimmable</b>	No
-----------------	----

#### Certificates & standards

<b>Type of protection</b>	IP20
<b>Standards</b>	CE/CB
<b>Energy efficiency class</b>	A+
<b>Energy efficiency class</b>	A+
<b>Energy consumption</b>	8 kWh/1000h

#### Country-specific categorizations

<b>ILCOS</b>	DR-7.6/840-G13-25.5/590
<b>Order reference</b>	ST8V-0.6M 7,6W/

#### Logistical data

<b>Temperature range at storage</b>	-20...80 °C
-------------------------------------	-------------

### EQUIPMENT / ACCESSORIES

- Suitable for operation with low-loss and conventional control gears

---

**SAFETY ADVICE**

Not suitable for operation with electronic control gear.

Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

---

**LOGISTICAL DATA**

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075024632	ST8V-EM 7.6 W/4000 K 600 mm EM	Shipping carton box 10	668 mm x 154 mm x 65 mm	6.69 dm <sup>3</sup>	1330.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**REFERENCES / LINKS**

For current information see

▶ [www.ledvance.com/substitute](http://www.ledvance.com/substitute)

---

**LEGAL ADVICE**

When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.