

DATA SHEET

REPAIRING KIT GF3

15-parts for GF3 fiberglass rod Ø 3 mm

Item no.: 20819



[Click here Video](#)

[Click here Productinformation](#)

Repair instruction

1. 10 min

2. CLEAN

Storable in accessory box

*Sample image - Box not included

DATA	
ITEM NO.	20819
WEIGHT	0,063 kg
DIMENSION	L 150 x B 150 x H 12 mm
Material	Stainless steel and brass
Content	15-parts
VOC content	2 % (special glue)
EAN-Code	9120045477276

- ### ADVANTAGES
- ✓ 15-parts
 - ✓ Very high yield
 - ✓ For repairing GF3 glass fibre rods
 - ✓ Fast solution
 - ✓ Dries within 10 minutes
 - ✓ Stainless steel / brass sleeves

DESCRIPTION

15-Part set for repairing glass fibre rods GF3 Ø 3 mm. The patented guiding head (external thread RTG Ø 6 mm) with twist adjustment is optimally suited for the GF3 glass fibre rod Ø 3 mm. The newly developed kink protection makes it possible to overcome bending radii of up to R = 38 mm. An extra large eyelet hole of the enclosed pulling eye ensures a higher cable capacity of up to 7 x 2.5 mm². One drop of the special adhesive is enough for approx. 3 - 5 cm² adhesive surface. Dries within 10 minutes - see safety data sheet for instructions! The mounting wrench can be used to tighten or loosen the guiding head with kink protection. Stainless steel

Application film: You can watch a short, very informative application film by scanning the QR code or at www.runpotec.com.

Scope of supply: 1 x guiding head with twist adjustment, 2 x kink protection, 2 x mounting wrench, 1 x pulling eye Ø 7 mm, 6 x adhesive joints (brass), 1 x coupling joint, 1 x starting bulb Ø 11 mm

INFORMATION

USE WITH:

Cable pulling system GF 3
Length: 20 m | 30m | 50m
Item no 10192 | 10193 | 10195

Replacement Fiberglass rod GF 3 Ø 3 mm:
Length: 20 m | 30m | 50m
Item no 20816 | 20817 | 20818

[Click here Productinformation](#)