


	ZPA1-2.5	ZPA2-2.5	ZPA2-2.5A
	<b>2,5 mm<sup>2</sup></b>	<b>2x2,5 mm<sup>2</sup></b>	<b>2x2,5 mm<sup>2</sup></b>
Colour   Cat. number	White ○	White ○	White ○
Standard	44 231 516	44 232 516	44 242 516
Certificate / Declaration	PN-EN 60998-1	PN-EN 60998-1	PN-EN 60998-1
Body	CE	CE	CE
Number of tracks	ceramic, enamelled	ceramic, enamelled	ceramic, enamelled
Rated cross-section	1	1	2
Current data	2,5 mm <sup>2</sup>	2,5 mm <sup>2</sup>	2,5 mm <sup>2</sup>
Rated voltage	500 V	500 V	500 V
Rated current	24 A	24 A	24 A
Operating temperature	-40 °C ... +230 °C	-40 °C ... +230 °C	-40 °C ... +230 °C
External dimensions			
A / B / C [mm]	11 / 19 / 25	19 / 18 / 26	24 / 19 / 26 / 14,5
Set screw - bolt	M3	M3	M3
Stripped wire length	5 mm	5 mm	5 mm
Mounting to the substrate Ø	-	-	2xM3
Weight	11 g	17 g	22 g
Additional information			fixing screw M3 x 16 (PN-M82215)
Collective packaging			



	ZPA2-10
	<b>2x10 mm<sup>2</sup></b>
Colour   Cat. number	White ○
Standard	44 532 516
Certificate / Declaration	PN-EN 60998-1
Body	CE
Number of tracks	ceramic, enamelled
Rated cross-section	2
Current data	10 mm <sup>2</sup>
Rated voltage	500 V
Rated current	57A
Operating temperature	-40 °C ... +230 °C
External dimensions	
A / B / C [mm]	28 / 20 / 28
Set screw - bolt	M4
Stripped wire length	8 mm
Mounting to the substrate Ø	1 x M4
Weight	45 g
Additional information	Fixing screw M4 x 20 (PN-M82215)
Collective packaging	