

Multiple socket of 2 sockets 2P+E, 16A 250V~. With light switch.

Multiple socket of 2 sockets 2P+E, 16A 250V~. With light switch. MAX. 3680W. White colour. Easy connection access. With fixing holes to the wall. Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Type	Multiple base
No. of bases	2
Basic characteristics	2P+E, 16A 250V~
Maximum power	3.680 W
Light switch	Yes
Terminal system	Screw connection
Mini trunking input	Yes, for 7x12, 10x16, 10x20 and 12x12
Possibility of using hanger	Yes
Possibility of using KIT-DIN35	Yes
Wall fixing holes	Yes

Technical data

Protection Degree (IP)	IP20
Fire resistance (GWT)	850°C
Heat resistance (Ball pressure)	125°C
Ambient operating temperature	-5°C ; +60°C
Free of halogens	Yes

Regulations

CE marking	Yes
According to Regulations UNE/EN	UNE-20315-1-1:2017; UNE-20315-1-2:2017

According to REBT	Yes
Intertek certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes


Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes

Logistics and packaging

Unit EAN code	8423220237520
EAN code container	8423220063631
EAN code packaging	18423220063638
Units packaging	12
Units carton	96
Pallet Units	3360
Packaging Measurements cm	17,8x19x14,3
Packaging Measures cm	59,5x20x37,5
Unit weight (gr)	149
Container Weight (Kg)	1,88
Packaging Weight (Kg)	15,62
Tariff code	85366990

Sketch





Documentation and downloads



[Assembly instructions \(0.67MB\)](#)



[Certificate \(0.33MB\)](#)