

## Presence detector

# HF 360

EAN 4007841002800



### Functional description

STEINEL's not only the pioneer of high-frequency sensor technology but also the first to use it successfully for presence detectors. With a whole host of benefits, specifically for applications in public areas, such as WC cubicles. Because HF works without any lens, the Presence Control PRO HF 360 is extremely slim and bears little resemblance with a "watchdog". This makes it hardly vulnerable to vandalism for example.

### Technical specifications

<b>Type</b>	Presence detector
<b>Dimensions (L x W x H)</b>	120 x 120 x 75 mm
<b>Mains power supply</b>	230 V, 50 / 60 Hz
<b>Sensor Technology</b>	High frequency
<b>Application, place</b>	Indoors
<b>Type of installation</b>	Concealed wiring
<b>HF-system</b>	5,8 GHz
<b>Electronic scalability</b>	Yes
<b>Mechanical scalability</b>	No
<b>Mounting height</b>	2,50 – 3,50 m
<b>Optimum mounting height</b>	2,8 m
<b>Detection</b>	also through glass, wood and stud walls
<b>Detection angle</b>	360 °
<b>Angle of aperture</b>	160 °
<b>Sneak-by guard</b>	Yes
<b>Capability of masking out individual segments</b>	Yes
<b>Reach, detail</b>	Zur Raumanpassung lassen sich 1 oder 2 Erfassungsrichtungen per Aufkleber ausblenden
<b>Reach, radial</b>	Ø 12 m (113 m <sup>2</sup> )
<b>Reach, tangential</b>	Ø 12 m (113 m <sup>2</sup> )
<b>Twilight setting TEACH</b>	Yes
<b>Twilight setting</b>	10 – 1000 lx
<b>Time setting</b>	30 s – 30 min
<b>Constant-lighting control</b>	No
<b>Basic light level function</b>	No
<b>With remote control</b>	No
<b>Interconnection</b>	Yes
<b>Type of interconnection</b>	Master/slave, Master/master
<b>IP rating</b>	IP20
<b>Material</b>	Plastic
<b>Ambient temperature</b>	-25 – 55 °C
<b>Colour</b>	white
<b>Colour, RAL</b>	9010
<b>Manufacturer's Warranty</b>	5 years

Data sheet



Presence detector

# HF 360

EAN 4007841002800

**Version**

COM1

---

Presence detector

## HF 360

EAN 4007841002800

### Sensorenerfassungsbereich 1

