



ONTEC S M1 301 M ST

TM-OS.M1.ST009




PARAMETERS

Standards	PN-EN 60598-1, PN-EN 60598-2-2, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838
Warranty	24 months - ST 36 months - AT 60 months - DATA, CB
Application	anti-panic lighting
IP	IP44
IK	IK08
Version	ST – for button test
Power supply	210+250 V AC 50+60 Hz
Temperature range	10-40 °C
Material	PC
Colour	white
Duration time	3 h
Operating mode	M
Maximum light power (the luminaire can power the light source with a different power)	2.3 W
Active power	5.8 W
Insulation class	2
Luminous flux	141 lm
Battery	Ni-Cd HT 3.6V 1.5Ah



PHOTOMETRY [m]



Ceiling height

2,5
3,0
4,0
5,0
6,0
7,0
8,0
9,0
10,0

Distance wall - fitting

3,0
3,2
3,4
3,6
3,6
3,4
3,0
2,6
2,4

Distance fitting - fitting

8,3
9,0
10,3
11,0
11,8
12,2
12,0
11,7
11,5

