4-CH NVR, 12MP, 4 PoE ports

1098/424P-WH

Product specifications:



- H.265 H265+ H.264 H264+
- IN/OUT bandwidth: 76/76 Mbps
- S.M.A.R.T. hard disk
- 4 IP channels
- 4 PoE ports
- Maximum resolution and recording speed: 12M, 8M (4K), 5M, 4M, 3M, 2M (1080P), 1.3M (960P), 1.0MP (720P) @ 25fps per single IP channel
- 1 HDD slot with max. capacity of 10TB
- Network port: 10/100 Mbps self-adaptive Ethernet interface
- 1 VGA output / 1 HDMI output (up to 4K)
- *Perimeter Intrusion Detection (PID), *Line Crossing Detection (LCD), *Stationary Object Detection (SOD), *Pedestrian Detection (PD), *Face Detection (FD), *Crossing Counting (CC), *Video Tampering, *Face Recognition, *Human & Vehicle Detection, *Heat Map, *Attribute Detection, *Face Attendance, *Crowd Detection (CD), *Queue Detection (QD), *Abnormal Sound Detection (RSD), *License Plate Detection (LPD) (*algorithms available depending on the camera model)
- HDD excluded
- Dimensions (W x H x D): 300 x 53 x 227 mm

Description

The NVR is fully remotely manageable from both Windows and MAC systems, and is compatible with UVS software, browsers, and the new free iUVS Pro app, which allows convenient management from all smartphones (Android and iOS), iPads, and tablets.
The NVR directly manages the smart V-DECT functions of IP cameras and offers compatibility with the range of Fisheye IP cameras (dewarping management only through the WEB page, iUVS software, and iUVS Pro app).
It features POE ports for direct power supply to connected IP cameras.

Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156082902**
- Base:
- Height:
- Depth:

Urmet S.p.A. reserves the right to make changes to its equipment at any time, without prior notice. The installation must be carried out by qualified personnel and in accordance with the rules relating to the installation of electrical equipment in force in the country where the products are installed.