

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Lackstift**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Lacquer
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
RITTAL GmbH & Co.KG  
Auf dem Stützelberg  
D-35745 Herborn  
Phone: +49 2772 505 0  
e-mail: info@rittal.de
- **1.4 Emergency telephone number:**  
Informationszentrale gegen Vergiftungen  
Tel.: 0228/19240 (Notfall)  
0228/287-3-3480 (Sekretariat)  
Fax: 0228/287-3-3278

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3      H226      Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2      H373      May cause damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Chronic 2 H411      Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2      H315      Causes skin irritation.

Eye Irrit. 2      H319      Causes serious eye irritation.

STOT SE 3      H335-H336      May cause respiratory irritation. May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.

**Trade name: Lackstift**

(Contd. of page 1)



**Xi; Irritant**

R37: Irritating to respiratory system.



**N; Dangerous for the environment**

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R10-66: Flammable. Repeated exposure may cause skin dryness or cracking.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms** GHS02, GHS07, GHS08, GHS09

· **Signal word** Warning

· **Hazard-determining components of labelling:**

Solvent naphtha (petroleum), light arom.

xylene

n-butyl acetate

Ethylbenzene

· **Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate, Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 04.02.2015

Version number 30

Revision: 04.02.2015

**Trade name: Lackstift**

(Contd. of page 2)

- **Labelling of packages where the contents do not exceed 125 ml**
- **Hazard pictograms** GHS02, GHS07, GHS08, GHS09
- **Signal word** Warning
- **Hazard-determining components of labelling:**  
Solvent naphtha (petroleum), light arom.  
xylene  
n-butyl acetate  
Ethylbenzene
- **Hazard statements**  
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.
- **Precautionary statements**  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P405 Store locked up.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64742-95-6 EC number: 918-668-5	Solvent naphtha (petroleum), light arom. ☒ Xn R65; ☒ Xi R37; ☒ N R51/53 R10-66-67 ----- ☠ Flam. Liq. 3, H226; ☠ Asp. Tox. 1, H304; ☠ Aquatic Chronic 2, H411; ☠ STOT SE 3, H335-H336	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene ☒ Xn R20/21; ☒ Xi R38 R10 ----- ☠ Flam. Liq. 3, H226; ☠ STOT RE 2, H373; Asp. Tox. 1, H304; ☠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	12.5-<20%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate R10-66-67 ----- ☠ Flam. Liq. 3, H226; ☠ STOT SE 3, H336	≤10%

(Contd. on page 4)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 30

Revision: 04.02.2015

**Trade name: Lackstift**

		(Contd. of page 3)
CAS: 13879-32-8 EINECS: 237-644-9	[1,1'-[methylenebis(oxyethane-1,2-diyloxy)]bisbenzene N R51/53 Aquatic Chronic 2, H411	3-<10%
CAS: 100-41-4 EINECS: 202-849-4	Ethylbenzene Xn R20; F R11 Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	3-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10 Flam. Liq. 3, H226	3-<10%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-butoxyethyl acetate Xn R20/21/22 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	1-≤2.5%
CAS: 41556-26-7 EINECS: 255-437-1 Reg.nr.: 01-2119491304-40	Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate Xi R43; N R50/53 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	0.3-<1%
CAS: 82919-37-7 EINECS: 280-060-4	Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Xi R43; N R50/53 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	0.1-<0.25%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

##### After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

##### After skin contact:

Immediately wash with water and soap and rinse thoroughly.

##### After eye contact:

Rinse opened eye for several minutes under running water.

##### After swallowing:

If symptoms persist consult doctor.

#### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

· **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 30

Revision: 04.02.2015

Trade name: Lackstift

(Contd. of page 4)

- **5.2 Special hazards arising from the substance or mixture**  
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**1330-20-7 xylene**

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm
	Sk; BMGV

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 04.02.2015

Version number 30

Revision: 04.02.2015

**Trade name: Lackstift**

(Contd. of page 5)

**123-86-4 n-butyl acetate**

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

**100-41-4 Ethylbenzene**

WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Sk

**108-65-6 2-methoxy-1-methylethyl acetate**

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

**112-07-2 2-butoxyethyl acetate**

WEL Short-term value: 332 mg/m<sup>3</sup>, 50 ppm  
Long-term value: 133 mg/m<sup>3</sup>, 20 ppm  
Sk

**· Ingredients with biological limit values:****1330-20-7 xylene**

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Protection of hands:** Not required.

· **Eye protection:** Not required.

## SECTION 9: Physical and chemical properties

**· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:**

**Form:** Fluid  
**Colour:** According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 30

Revision: 04.02.2015

**Trade name: Lackstift**

(Contd. of page 6)

· <b>Change in condition</b> <b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	124 °C
· <b>Flash point:</b>	30 °C (DIN 53213)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	370 °C (DIN 51794)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	0.7 Vol %
<b>Upper:</b>	7.5 Vol %
· <b>Vapour pressure at 20 °C:</b>	10.7 hPa
· <b>Density at 20 °C:</b>	1.03 g/cm <sup>3</sup> (DIN 53217)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic at 20 °C:</b>	220 s (DIN 53211/4)
· <b>Solvent content:</b>	
<b>VOC (EC)</b>	65.19 %
<b>Solids content (weight-%):</b>	35.1 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

GB

(Contd. on page 8)

Trade name: Lackstift

(Contd. of page 7)

## SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity:

- LD/LC50 values relevant for classification:

### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2000 mg/kg (rab)
--------	------	-------------------

### 1330-20-7 xylene

Oral	LD50	8700 mg/kg (rat)
------	------	------------------

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitisation: No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful  
Irritant

## SECTION 12: Ecological information

- 12.1 Toxicity
  - Aquatic toxicity: No further relevant information available.
  - 12.2 Persistence and degradability No further relevant information available.
  - 12.3 Bioaccumulative potential No further relevant information available.
  - 12.4 Mobility in soil No further relevant information available.
  - Ecotoxicological effects:
  - Remark: Toxic for fish
  - Additional ecological information:
  - General notes:
- Water hazard class 2 (German Regulation) : hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- 12.5 Results of PBT and vPvB assessment
  - PBT: Not applicable.
  - vPvB: Not applicable.
  - 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
  - Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)



**Trade name: Lackstift**

(Contd. of page 8)

· **European waste catalogue**

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

· **14.1 UN-Number**  
· **ADR, IMDG, IATA**

UN1263

· **14.2 UN proper shipping name**  
· **ADR**

1263 PAINT, ENVIRONMENTALLY HAZARDOUS,  
special provision 640E

· **IMDG**

PAINT (Solvent naphtha, [1,1'-  
[methylenebis(oxyethane-1,2-diyloxy)]bisbenzene),  
MARINE POLLUTANT

· **IATA**

PAINT

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**  
· **Label**

3 (F1) Flammable liquids.  
3

· **IMDG**



· **Class**  
· **Label**

3 Flammable liquids.  
3

· **IATA**



· **Class**  
· **Label**

3 Flammable liquids.  
3

· **14.4 Packing group**  
· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**

Product contains environmentally hazardous  
substances: piperidyl sebacates, Solvent naphtha

· **Marine pollutant:**

Yes  
Symbol (fish and tree)

(Contd. on page 10)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 30

Revision: 04.02.2015

**Trade name: Lackstift**

(Contd. of page 9)

· <b>Special marking (ADR):</b>	Symbol (fish and tree)
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	30
· <b>EMS Number:</b>	F-E,S-E
· <b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
-----	
· <b>ADR</b>	
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	D/E
-----	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>UN "Model Regulation":</b>	UN1263, PAINT, special provision 640E, ENVIRONMENTALLY HAZARDOUS, 3, III

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **National regulations:**

Class	Share in %
NK	50-100

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
-----	
R10	Flammable.

(Contd. on page 11)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2015

Version number 30

Revision: 04.02.2015

**Trade name: Lackstift**

(Contd. of page 10)

- R11 *Highly flammable.*  
 R20 *Harmful by inhalation.*  
 R20/21 *Harmful by inhalation and in contact with skin.*  
 R20/21/22 *Harmful by inhalation, in contact with skin and if swallowed.*  
 R37 *Irritating to respiratory system.*  
 R38 *Irritating to skin.*  
 R43 *May cause sensitisation by skin contact.*  
 R50/53 *Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*  
 R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*  
 R65 *Harmful: may cause lung damage if swallowed.*  
 R66 *Repeated exposure may cause skin dryness or cracking.*  
 R67 *Vapours may cause drowsiness and dizziness.*

• **Abbreviations and acronyms:**

- RID: *Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*  
 ICAO: *International Civil Aviation Organisation*  
 ADR: *Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*  
 IMDG: *International Maritime Code for Dangerous Goods*  
 IATA: *International Air Transport Association*  
 GHS: *Globally Harmonised System of Classification and Labelling of Chemicals*  
 EINECS: *European Inventory of Existing Commercial Chemical Substances*  
 ELINCS: *European List of Notified Chemical Substances*  
 CAS: *Chemical Abstracts Service (division of the American Chemical Society)*  
 VOC: *Volatile Organic Compounds (USA, EU)*  
 LC50: *Lethal concentration, 50 percent*  
 LD50: *Lethal dose, 50 percent*  
 Flam. Liq. 2: *Flammable liquids, Hazard Category 2*  
 Flam. Liq. 3: *Flammable liquids, Hazard Category 3*  
 Acute Tox. 4: *Acute toxicity, Hazard Category 4*  
 Skin Irrit. 2: *Skin corrosion/irritation, Hazard Category 2*  
 Eye Irrit. 2: *Serious eye damage/eye irritation, Hazard Category 2*  
 Skin Sens. 1: *Sensitisation - Skin, Hazard Category 1*  
 STOT SE 3: *Specific target organ toxicity - Single exposure, Hazard Category 3*  
 STOT RE 2: *Specific target organ toxicity - Repeated exposure, Hazard Category 2*  
 Asp. Tox. 1: *Aspiration hazard, Hazard Category 1*  
 Aquatic Acute 1: *Hazardous to the aquatic environment - Acute Hazard, Category 1*  
 Aquatic Chronic 1: *Hazardous to the aquatic environment - Chronic Hazard, Category 1*  
 Aquatic Chronic 2: *Hazardous to the aquatic environment - Chronic Hazard, Category 2*

- \* **Data compared to the previous version altered.**